

**LIQUID CRYSTAL DISPLAY ELEMENT AND ITS PRODUCTION**

Patent Number: JP11133438  
Publication date: 1999-05-21  
Inventor(s): MIYATA SHINICHI; TANAKA YOSHINORI; YAMAZAKI ATSUSHI  
Applicant(s): MATSUSHITA ELECTRIC IND CO LTD  
Requested Patent: ☐ JP11133438  
Application Number: JP19970309669 19971024  
Priority Number(s):  
IPC Classification: G02F1/1339 ; G02F1/1339 ; G09F9/30  
EC Classification:  
Equivalents:

**Abstract**

**PROBLEM TO BE SOLVED:** To maintain the spraying uniformity of spacers, to enhance adhesion property between substrates and to improve a display grade by using ferromagnetic spacers and using magnetic field for holding the ferromagnetic spacers between glass substrates.

**SOLUTION:** The glass substrates with ITO electrodes are used for the substrate A and the substrate B and the ferromagnetic material spacers C are used for the spacers. The spacers C are sprayed by using a dry process spraying device by nitrogen blow. An acrylic resin material is used for an end-sealing material D. Further, the uniform magnetic field by a solenoid device is applied to the magnetic field F. The substrate A and the substrate B are bonded to each other by the end-sealing material D of an acrylic resin material within the magnetic field F, by which the ferromagnetic material spacers C are uniformly dispersed to the prescribed positions without movement between the substrate A and the substrate B. As a result, the spacing between the substrate A and the substrate B is made uniform and the execution of the uniform display is made possible.

Data supplied from the esp@cenet database - 12